

CHAPTER 7

SURFACE RADAR REPORTING

7.1. General. Radar observations of tropical cyclones will be made at Department of Defense (DOD), National Weather Service (NWS), and Federal Aviation Administration (FAA) Weather Surveillance Radar-1988 Doppler (WSR-88D) facilities. Participating radar sites are listed in Table 7-1.

7.2. The WSR-88D. The WSR-88D is a computerized radar data collection and processing system. The design and implementation of the WSR-88D was a joint effort of the DOD, NWS, and FAA, and the utilization of the radar continues to be governed by tri-agency agreement. The WSR-88D is an S-band (10-cm), coherent radar, with a nominal beam width of 1 degree. The maximum data ranges are 248 nm (reflectivity) and 124 nm (velocity). Radar scanning strategies are selectable, using predetermined volume coverage patterns (VCP). The VCP in use depends upon which weather phenomena are under surveillance. Once the radar data has been collected, it is processed automatically at the radar site by a suite of algorithms which provide graphical products for forecaster use. TPC/NHC, as an external user, obtains these products through a *network* connection. CPHC controls and operates four WSR-88Ds in Hawaii and obtains products directly.

7.3. Procedures. As a tropical cyclone approaches, TPC/NHC uses the WSR-88D to perform radar center-fixing and to obtain other diagnostic information. Therefore, it is important to optimize WSR-88D performance for tropical cyclones and to allow other users, especially the TPC/NHC, access to radar products in the area of landfall. Most of the changes must be issued through the Master System Control Function (MSCF), Human Computer Interface (HCI). To facilitate this process, TPC/NHC in cooperation with the Radar Operations Center (ROC) has developed an operations plan for use during tropical cyclone events. The current tropical cyclone operations plan is available as a sub-link to the National Hurricane Operations Plan on the OFCM web site at <http://www.ofcm.gov/homepage/text/pubs.htm>. It is also available via fax from the ROC Hotline (1-800-643-3363).

7.3.1. Radar Observation Requirements, WSR-88D. Chief among the requirements is the appropriate display of hurricane-force winds. Changes must be made at the radar site, guided by the WSR-88D Tropical Cyclone Operations Plan, in order to deal effectively with hurricane conditions. The physical characteristics of the tropical cyclone are best represented by use of the precipitation mode, usually VCP 11, 21 *or* 121, depending upon range. Radar characteristics of hurricanes are given in Federal Meteorological Handbook Number 11 (FMH-11), Part B, Chapter 9. Further discussion of product usage appears in FMH-11, Part D, Unit Description and Operational Applications. A recommended product list appears in FMH-11 Part D, Application versus Product Table 4-1.

Table 7-1. Participating radar stations ¹

LOCATION	RADAR TYPE	LATITUDE	LONGITUDE
NATIONAL WEATHER SERVICE RADARS			
<u>U.S. Gulf and Atlantic coast</u>			
Albany, NY	WSR-88D	42E35' N	74E04' W
Atlanta, GA	WSR-88D	33E22' N	84E34' W
Binghamton, NY	WSR-88D	42E12' N	75E59' W
Birmingham, AL	WSR-88D	33E10' N	86E46' W
Boston, MA	WSR-88D	41E57' N	71E08' W
Brandon/Jackson, MS	WSR-88D	32E17' N	89E59' W
Brownsville, TX	WSR-88D	25E55' N	97E25' W
Caribou, ME	WSR-88D	46E02' N	67E48' W
Charleston, SC	WSR-88D	32E33' N	80E47' W
Columbia, SC	WSR-88D	32E39' N	81E03' W
Corpus Christi, TX	WSR-88D	27E47' N	97E31' W
Ft. Worth, TX	WSR-88D	32E34' N	97E18' W
Greer, SC	WSR-88D	34E53' N	82E13' W
Houston, TX	WSR-88D	29E28' N	95E05' W
Huntsville/Hytop, AL	WSR-88D	34E56' N	86E05' W
Jacksonville, FL	WSR-88D	30E29' N	81E42' W
Key West, FL	WSR-88D	24E36' N	81E42' W
Lake Charles, LA	WSR-88D	30E07' N	93E13' W
Melbourne, FL	WSR-88D	28E07' N	80E39' W
Miami, FL	WSR-88D	25E37' N	80E25' W
Mobile, AL	WSR-88D	30E41' N	88E15' W
Morehead City, NC	WSR-88D	34E46' N	76E53' W
New Orleans/Baton Rouge LA	WSR-88D	30E20' N	89E50' W
New York City, NY	WSR-88D	40E52' N	72E52' W
Philadelphia, PA	WSR-88D	39E57' N	74E25' W
Portland, ME	WSR-88D	43E53' N	70E15' W
Raleigh/Durham, NC	WSR-88D	35E40' N	78E29' W
Roanoke, VA	WSR-88D	37E01' N	80E16' W
San Antonio, TX	WSR-88D	30E43' N	97E23' W
Shreveport, LA	WSR-88D	32E27' N	93E50' W
State College, PA	WSR-88D	40E55' N	78E00' W
Sterling, VA	WSR-88D	38E58' N	77E29' W
Tallahassee, FL	WSR-88D	30E24' N	84E20' W
Tampa, FL	WSR-88D	27E42' N	82E24' W
Wakefield, VA	WSR-88D	36E59' N	77E00' W
Wilmington, NC	WSR-88D	33E59' N	78E26' W

¹The criterion for selection is that the radar site is located within approximately 124 n mi (maximum velocity range) of the coastline.

NATIONAL WEATHER SERVICE RADARS
U.S. Southwest

Phoenix, AZ	WSR-88D	33E17' N	111E40' W
San Diego, CA	WSR-88D	33E49' N	117E38' W
Tucson, AZ	WSR-88D	31E57' N	110E54' W
Yuma, AZ	WSR-88D	32E40' N	114E37' W

FAA RADARS

Molokai, HI	WSR-88D	21E08'N	157E11'W
Kohala, HI	WSR-88D	20E06'N	155E45'W
San Juan, PR	WSR-88D	18E07'N	66E05'W
South Hawaii, HI	WSR-88D	19E06'N	155E34'W
South Kauai, HI	WSR-88D	21E54'N	159E33'W

DEPARTMENT OF DEFENSE

<i>Andersen AFB, Guam</i>	<i>WSR-88D</i>	<i>13E27'N</i>	<i>144E49'E</i>
Columbus AFB, MS	WSR-88D	33E54'N	88E20'W
Dover AFB, DE	WSR-88D	38E50'N	75E26'W
Eglin AFB, FL	WSR-88D	30E34'N	85E55'W
Fort Hood, TX	WSR-88D	30E43'N	97E23'W
Fort Polk, LA	WSR-88D	31E09'N	92E58'W
Fort Rucker, AL	WSR-88D	31E28'N	85E28'W
Maxwell AFB, AL	WSR-88D	32E32'N	85E47'W
Moody AFB, GA	WSR-88D	30E33'N	83E00'W
Robins AFB, GA	WSR-88D	32E40'N	83E21'W

(NHC has dial-in access to the above DOD sites.)

7.3.2. Central Region Report. The following fix definitions and criteria are used in reporting WSR-88D tropical cyclone radar observations:

- If the central region of a storm is defined by an identifiable circular, or nearly circular, wall cloud with an echo-free center, the fix (the geometric center) is reported as an **"EYE"**.
- If the central region is recognizable, but not well-defined by a wall cloud (as in the case of a tropical storm), it is reported as a **"CENTER."**
- When the eye or center is only occasionally recognizable or some other central region uncertainty exists, the eye or center is reported as **"PSBL EYE"** or **"PSBL CENTER."**

- Remarks stating the degree of confidence will be included and will be classified as either "good," "fair," or "poor." If an eye is present, a "good" fix is reported when the eye is symmetrical--virtually surrounded by wall cloud; a "poor" fix is reported when the eye is asymmetrical--less than 50 percent surrounded by wall cloud; a "fair" fix is reported to express a degree of confidence between "good" and "poor." Note that a partial eyewall may be the result of excessive range from the radar, or represent the true structure of the system. Doppler velocities will, in general, increase confidence in the center position and, if available, should always be examined prior to establishing a fix.

7.3.3. Transmission of Radar Reports. When the tropical cyclone is within 200 n mi of a WSR-88D, and the center fix is considered reliable, the appropriate tropical cyclone warning center (TPC/NHC or CPHC) may issue a tropical cyclone position estimate (AFOS category TCE) between 2-hourly intermediate advisories. Note that although the issuance of this product depends upon the quality of the radar fix, other data sources such as aircraft reconnaissance may be blended with the radar estimate to obtain a position. Thus, a radar position based on a particular radar may appear to disagree with the TCE position, but has in fact been taken into consideration.

In the case of communications failure, and the event that TPC/NHC cannot obtain the necessary radar data, the local NWS Weather Forecast Office may be called upon to estimate the radar position and render qualitative assessment of the circulation.

Other radar facilities not having weather transmission capability but wishing to provide information deemed important, should call the nearest NWS Weather Forecast Office or the TPC/NHC.